

Led & Led

Leader in Led solutions


▼ When you need to install or disassemble this light, you must turn off the power and have professionals work

▼ Our products comply with CIE 127: 2007; IEC 62031: 2008; IEC / PAS 62612: 2009 international standard

▼ All products company warranty policy statement as our website

LED DOMO Street Lamp

Datesheet




| | | |
|---|-----------|---|
| § | Material: | Aluminium+PC |
| § | Base: | E26 E27 E39 E40 B22 |
| § | CCT: | 2700K-7500K |
| § | CRI: | >Ra 82; >Ra 90 |
| § | Chip: | Samsung SMD 5630 ,5730 |
| § | Driver | Internal : Own 27W-65W External : Meanwell } 80W |





| | Power | 27W | 36W | 45W | 54W | 80W | 100W | 120W |
|--|-------|-----|-----|-----|-----|-----|------|------|
|--|-------|-----|-----|-----|-----|-----|------|------|

| | | | | | | | | |
|---------------------|------|------|------|------|------|------|------|---|
| Thermal glue | ✓ | ✓ | ✓ | ✓ | | | | |
| External Driver | | | | | | ✓ | ✓ | ✓ |
| Heat sink | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Length (H) | 200 | 225 | 250 | 265 | 285 | 325 | 360 | |
| Diameter (D) | 93 | 93 | 93 | 93 | 120 | 120 | 120 | |
| Weight | 0.87 | 0.97 | 1.07 | 1.17 | 2.4 | 2.52 | 2.62 | |
| Beam Angle | 360 | 360 | 360 | 360 | 360 | 360 | 360 | |
| Efficiency (lm/w) | ~140 | ~140 | ~140 | ~140 | ~140 | ~140 | ~140 | |
| chip quantity (Pcs) | 81 | 108 | 135 | 162 | 240 | 300 | 336 | |



Size
mm; kg



cal