

Test Report: DPL-45-24

45W Single Output LED Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 2.7 Vp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 1.03 Vp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 24 V ~ 26 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	21.47 V ~ 26.74 V / 230 VAC 21.47 V ~ 26.72 V / 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : -10 % ~ 10 % (Max)	I/P : 100VAC / 295 VAC O/P : FULL / MIN LOAD Ta : 25°C	V1 : -2.4 % ~ 2.4 %	P
4	LINE REGULATION	V1 : -3 % ~ 3 % (Max)	I/P : 100VAC ~ 295 VAC O/P : FULL LOAD Ta : 25°C	V1 : -0.4 % ~ 0.4 %	P
5	LOAD REGULATION	V1 : -5 % ~ 5 % (Max)	I/P : 230 VAC O/P : FULL ~ MIN LOAD Ta : 25°C	V1 : -0.45 % ~ 0.45 %	P
6	SET UP TIME	230VAC : 1500 ms (Max) 115VAC : 3000 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC / 1019 ms 115VAC / 2038 ms	P
7	OVER/UNDERSHOOT TEST	< ±10%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 10 %	P
8	CONSTANT CURRENT OPERATION VOLTAGE	18V ~ 24 V	I/P : 230 VAC I/P : 115 VAC O/P : CV MODE Ta : 25°C	230VAC / 15.16V~24 V 115VAC / 15.2V~24 V	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90 VAC~ 295 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V= 87V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	71V~295V TEST : OK	P
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 90 VAC ~ 295 VAC O/P : FULL-MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.9 / 230 VAC(TYP) 0.92 / 115 VAC(TYP) 0.9 / 277VAC(TYP)	I/P : 230 VAC I/P : 115VAC I/P : 277VAC O/P : 100% LOAD Ta : 25°C	PF= 0.94 / 230VAC PF= 0.99 / 115VAC PF= 0.903 / 277VAC	P
4	EFFICIENCY	86.5 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	87 %	P
5	INPUT CURRENT	230V/ 0.25 A 115V/ 0.55 A	I/P : 230 VAC I/P : 115VAC O/P : FULL LOAD Ta : 25°C	I= 0.22 A/ 230 VAC I= 0.42 A/ 230 VAC	P
6	INRUSH CURRENT	230V/ 40 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I= 35 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.75 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.28 mA N-FG : 0.26 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95%~110%	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	106%/ 230 VAC 106%/ 115 VAC Constant Current Limiting	P
2	OVER VOLTAGE PROTECTION	CH1 : 28V~ 32V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	30.98V/ 230 VAC 31.05V/ 115 VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 95 ± 10°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

CONTROL FUNCTION TEST

1	CURRENT ADJ. RANGE	3 % ~ -25 %	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	0.873 A ~ 2.799 A/230VAC 0.873 A ~ 2.802 A/115 VAC	P
---	--------------------	-------------	---	---	---

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : 2SK4111 10A/600V	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 562 V (2) 498 V (3) 556 V	P
2	Diode Peak Voltage	D100 Rated : BYV32E-200 20A/200V	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 157 V (2) 127 V (3) 150 V	P
3	Clamp Diode Peak Voltage	D 2 Rated : 2A/800V GP20K	I/P : High-Line +3V = 298 V O/P : (1)Full load continue Ta : 25°C	(1) 490 V	P
4	Control IC Voltage Test	U1 Rated : PWM TDA4863G 10.5V~ 22 V	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 15.435 V (2) 13.631 V (3) 13.623 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75KVAC/min I/P-FG : 1.5 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 4.2 KVAC/min I/P-FG : 2.25 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 4.98 mA I/P-FG : 4.21 mA O/P-FG : 2.38 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 30 GΩ I/P-FG : 23.6 GΩ O/P-FG : 30 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	41 mΩ	P
4	APPROVAL	TUV : Certificate NO : UL : File NO :			N/A

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS C	I/P : 230 VAC/50HZ O/P : 95% LOAD/75%LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : 95% LOAD /50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : 95% LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : 95% LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : 95% LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 1KV L,N-PE : 2KV	I/P : 230 VAC/50HZ O/P : 95% LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																							
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P : 230VAC O/P : FULL LOAD Ta= 27.9 °C 2. HIGH AMBIENT BURN-IN : 4 HRS I/P : 230VAC O/P : FULL LOAD Ta= 43 °C	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 27.9 °C</th> <th>HIGH AMBIENT Ta= 43 °C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>BD1</td> <td>4A/800V SILICON US4KB80R-7000</td> <td>59.1°C</td> <td>68.9°C</td> </tr> <tr> <td>2</td> <td>Q1</td> <td>TK10B60D 10A/600V</td> <td>69.6°C</td> <td>78.9°C</td> </tr> <tr> <td>3</td> <td>D2</td> <td>3A/600V GP30J</td> <td>84.0°C</td> <td>90.9°C</td> </tr> <tr> <td>4</td> <td>C46</td> <td>100u/50V UL7Kh 8*11.5 KY</td> <td>64.2°C</td> <td>72.8°C</td> </tr> <tr> <td>5</td> <td>T1 COIL</td> <td>TF1547A-R0</td> <td>69.5°C</td> <td>77.8°C</td> </tr> <tr> <td>6</td> <td>D100</td> <td>BYV32E-200 20A/200V</td> <td>63.9°C</td> <td>73.9°C</td> </tr> <tr> <td>7</td> <td>C106</td> <td>1000u/35V UL10Kh 12.5*20 KY</td> <td>61.6°C</td> <td>71.1°C</td> </tr> <tr> <td>8</td> <td>TSW1</td> <td>ST-22W-R0 95°C 60mm</td> <td>61.5°C</td> <td>71.1°C</td> </tr> <tr> <td>9</td> <td>U1</td> <td>PWM TDA4863G</td> <td>69.5°C</td> <td>77.1°C</td> </tr> <tr> <td>10</td> <td>C8</td> <td>224/450V 10% P=10 MMX</td> <td>67.8°C</td> <td>76.8°C</td> </tr> </tbody> </table>	NO	Position	P/N	ROOM AMBIENT Ta= 27.9 °C	HIGH AMBIENT Ta= 43 °C	1	BD1	4A/800V SILICON US4KB80R-7000	59.1°C	68.9°C	2	Q1	TK10B60D 10A/600V	69.6°C	78.9°C	3	D2	3A/600V GP30J	84.0°C	90.9°C	4	C46	100u/50V UL7Kh 8*11.5 KY	64.2°C	72.8°C	5	T1 COIL	TF1547A-R0	69.5°C	77.8°C	6	D100	BYV32E-200 20A/200V	63.9°C	73.9°C	7	C106	1000u/35V UL10Kh 12.5*20 KY	61.6°C	71.1°C	8	TSW1	ST-22W-R0 95°C 60mm	61.5°C	71.1°C	9	U1	PWM TDA4863G	69.5°C	77.1°C	10	C8	224/450V 10% P=10 MMX	67.8°C	76.8°C		P
NO	Position	P/N	ROOM AMBIENT Ta= 27.9 °C	HIGH AMBIENT Ta= 43 °C																																																								
1	BD1	4A/800V SILICON US4KB80R-7000	59.1°C	68.9°C																																																								
2	Q1	TK10B60D 10A/600V	69.6°C	78.9°C																																																								
3	D2	3A/600V GP30J	84.0°C	90.9°C																																																								
4	C46	100u/50V UL7Kh 8*11.5 KY	64.2°C	72.8°C																																																								
5	T1 COIL	TF1547A-R0	69.5°C	77.8°C																																																								
6	D100	BYV32E-200 20A/200V	63.9°C	73.9°C																																																								
7	C106	1000u/35V UL10Kh 12.5*20 KY	61.6°C	71.1°C																																																								
8	TSW1	ST-22W-R0 95°C 60mm	61.5°C	71.1°C																																																								
9	U1	PWM TDA4863G	69.5°C	77.1°C																																																								
10	C8	224/450V 10% P=10 MMX	67.8°C	76.8°C																																																								
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : FULL LOAD O/P SHORT Ta : 25°C	TEST : OK	P																																																							
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 295VAC/100VAC O/P : 100 % LOAD Ta= -30 °C	TEST : OK	P																																																							
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL °C NO DAMAGE	I/P : 295 VAC O/P : FULL LOAD Ta= 40 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																							
5	TEMPERATURE COEFFICIENT	± 0.03 % (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.015 % (0~50°C)	P																																																							
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																							
7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -35°C~ +45°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load		OK	P																																																							

DPL-45T

8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
9	CAPACITOR LIFE CYCLE	PLN-45-24 : SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 40 °C LIFE TIME	(1) 303310HRS (2) 158147.5HRS	P
10	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 497.8K HRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 20,000 hours @ Tcase 70°C ; 50,000 hours @ Tcase 55°C		P