

## Fluoled DOMO series - 180° Rotative socket

### • Applications:

- Commercial and warehouse spaces
- General lighting
- Arquitectural lighting
- Museums lighting (without UV)
- Non toxic
- Dose not contain mercury (Hg), lead (Pb) or phosphorus
- No light flicker
- CE & ROHS
- Instant start. Even in cold
- 50% or more in reduction of consumption
- There is no loss of the light in the reflector
- Bright light output. Comparable to traditional fluorescent tubes
- Durable construction
- Glass resistant



The LED lighting tubes, provides an innovative durable alternative, non-toxic and large energy savings in comparison with the conventional tube  
Its lifetime can be 10 times higher than conventional fluorescent tubes (CFLd)

	<i>FLUOLED 60 SMD DOMO</i>	<i>FLUOLED 120 SMD DOMO</i>
Voltage	AC 85V-265V, - 50Hz/60Hz	AC 85V-265V, - 50Hz/60Hz
Current	240mA	470 mA
Power	8W	15W
Flux	550 lm	980 lm
Led quantity	68 P C S	120PCS
Construction	Aluminum & PC	Aluminum & PC
Size	T8 600mm	T8 1200mm
Color temperature	3000-4000K - 5500-6500K	3000-4000K - 5500-6500K
CRI / RA	≥ 75 / 85	≥ 75 / 85
Protection	IP20	IP20
Tube	T8	T8
Energy Efficiency	94%	94%
Lm/W	65 lm/w	65 lm/w
Operating temperature	- 40°C ~ + 50°C	- 40°C ~ + 50°C
Operating humidity	≤ 95%	≤ 95%