

Outdoor full color Real P10 quotation and specification

Part I Module		
1	Physical Pitch	10 mm
2	Pixel Arrangement	1Red 1Green1 Blue (DIP)
3	Pixel Density	10000dots/m ²
4	Resolution	16dots×16dots
5	Size	160mm (L)×160mm (H)
6	Drive Mode	Dynamic 1/4 Duty constant current driver
Part II Iron Fixed Cabinet		
7	Size	960mm (L) × 960mm(H)
8	Resolution	96dots (L) ×96dots (H)
9	Weight	50kgs
Part III Panel		
10	Dimension	1.92m (L) × 0.96m (H) = 1.84m²
11	Physical Resolution	192dots (L) × 96dots (H)
12	Quantity	2(L)×1(H)units = 2 Units
13	Weight	100kg
14	Best Minimum Viewing Distance	10m
15	Maximum Power Consumption	1000w/ m ²
16	Average Power Consumption	350w/ m ²
17	Grey Level	10 bits/1024levels
18	Viewing Angle	Horizontal 110°,Vertical 50°
19	Brightness	≥6000cd/ m ²
20	Refresh Rate	240-1000HZ
21	Control Method	Controlled by PC
22	Video Input	DVI
23	Communication Cable	UTP Category 5
24	MTBF	≥5,000 Hours
25	Life	≥100,000 Hours
26	Input Voltage	AC90V-260v, 50Hz-60Hz
27	Operating Temperature	-40℃ – +65℃
28	International Protection	IP65
Part IV System		

29	Operating System	Windows
30	Control System (Asynchronous system)	DBA 9.0
31	Price for LED panel	
32	Receiver card (DBA 9.0)	
33	Wireless modules (CPE)	
34	Total Amount	
Part V Others		