

Outdoor full color P10 quotation and specification

Part I Module		
1	Pixel Pitch	10mm
2	Pixel Arrangement	1R1G1 B
3	Pixel Density	1000dots/m ²
4	Resolution	16dots×16dots
5	Size	160mm (L) × 160mm (H)
6	Drive Mode	Dynamic 1/4 Duty Constant Current Driver
Part II Cabinet (Fixed installation cabinet)		
7	Size	960mm (L) ×960m(H)
8	Resolution	96dots (L) × 96dots (H)
9	Weight	55kg
Part III Screen		
10	Dimension	3.84m (L) ×2.88m (H) = 11.06m²
11	Cabinet Quantity	4(L)×3(H)units = 12Units
12	Physical Resolution	384dots (L) × 288dots (H)
13	Weight	660 kg
14	Best Minimum Viewing Distance	10m
15	Maximum Power Consumption	1000w/ m ²
16	Average Power Consumption	350w/ m ²
17	Grey Level	10 bits/1024levels
18	Viewing Angle	Horizontal 110°,Vertical 50°
19	Brightness	≥6000cd/ m ²
20	Refresh Rate	240-1000HZ
21	Control Method	Controlled by PC
22	Video Input	DVI
23	Communication Cable	UTP Category 5
24	MTBF	≥5,000 Hours
25	Life	≥100,000 Hours
26	Input Voltage	AC90V-260v, 50Hz-60Hz
27	Operating Temperature	-40°C - +65°C
28	International Protection	IP65 (Front and Back)

Part IV System		
29	Operating System	Windows
30	Control System	LINSN hard ware and software
31	Input Source Support	Composite, S-video, Component, VGA, DVI,HDMI,SDI,HD-SDI
32	Control distance	UTP CAT5E: 100m, Multi-mode Fiber: 500m , Single-mode Fiber 10Km
Part V Package & Spare Part		
33	Package	Carton package inside of exterior wooden case (Free)
34	Spares parts	4 pcs modules, 2pc power supplies, 1 receiving card, 4hub card, 1pcs Long power cable,1 pc long data cable, 15 pc short power cables,15 pc short data cables, 150 set RGB LEDs, several screws and accessories.
35		
36		
37		
38		