

Outdoor full color P16 quotation and specification

Part I Module		
1	Pixel Pitch	16mm
2	Pixel Arrangement	2R 1G 1 B
3	Pixel Density	3906dots/m ²
4	Resolution	16dots×8dots
5	Size	256mm (L) × 128 mm (H)
6	Drive Mode	Static constant current driver
Part II Cabinet (Fixed installation cabinet)		
7	Size	1024mm (L) ×768m(H)
8	Resolution	64dots (L) ×48dots (H)
9	Weight	47kgs
Part III Screen		
10	Dimension	8.192m (L) × 4,608m (H) = 37,75m ²
11	Cabinet Quantity	8(L)×6(H)units = 48 Units
12	Physical Resolution	512dots (L) × 240dots (H)
13	Weight	2256 kg
14	Best Minimum Viewing Distance	11m
15	Maximum Power Consumption	1000w/ m ²
16	Average Power Consumption	350w/ m ²
17	Grey Level	10 bits/1024levels
18	Viewing Angle	Horizontal 110°,Vertical 50°
19	Brightness	≥6000cd/ m ²
20	Refresh Rate	240-1000HZ
21	Control Method	Controlled by PC
22	Video Input	DVI
23	Communication Cable	UTP Category 5
24	MTBF	≥5,000 Hours
25	Life	≥100,000 Hours
26	Input Voltage	AC 90V-260v, 50Hz-60Hz
27	Operating Temperature	-40 °C — +65 °C
28	International Protection	IP65
Part IV System		
29	Operating System	Windows
30	Control System	LINSN hard ware and software

31	Input Source Support	Composite, S-video, Component, VGA, DVI,HDMI,SDI,HD-SDI
32	Control distance	UTP CAT5E: 100m, Multi-mode Fiber: 500m, Single-mode Fiber 10Km
Part V Package & Spare Part		
33	Package	Carton package inside of exterior wooden case (Free)
34	Spares parts	8 pcs modules, 2pc power supplies, 2 receiving card, 6hub card, 1pcs Long power cable,1 pc long data cable, 15 pc short power cables,15 pc short data cables, 150 set RGB LEDs, several screws and accessories.
35		
36		
37		
38		