

Outdoor full color P16 quotation and specification

Part I Module		
1	Pixel Pitch	16mm
2	Pixel Arrangement	2R1G1 B
3	Pixel Density	3906dots/m ²
4	Resolution	16dots×8dots
5	Size	256mm (L) × 128 mm (H)
6	Drive Mode	Static constant current driver
Part II Cabinet (Fixed installation cabinet)		
7	Size	1024mm (L) ×768mm(H)
8	Resolution	64dots (L) ×48dots (H)
9	Weight	54kg
Part III Screen		
10	Dimension	4.096m (L) × 3.072m (H) = 12.58m²
11	Cabinet Quantity	4(L)×4(H)units = 16Units
12	Physical Resolution	256dots (L) × 192dots (H)
13	Weight	864 kg
14	Best Minimum Viewing Distance	16m
15	Maximum Power Consumption	1000w/ m ²
16	Average Power Consumption	350w/ m ²
17	Grey Level	10 bits/1024levels
18	Viewing Angle	Horizontal 110°,Vertical 50°
19	Brightness	≥6000cd/ m ²
20	Refresh Rate	240-1000HZ
21	Control Method	Controlled by PC
22	Video Input	DVI
23	Communication Cable	UTP Category 5
24	MTBF	≥5,000 Hours
25	Life	≥100,000 Hours
26	Input Voltage	AC90V-260v, 50Hz-60Hz
27	Operating Temperature	-40°C - +65°C
28	International Protection	IP65 (Front and back)

Part IV System		
29	Operating System	Windows
30	Control System	LINSN hard ware and software
31	Input Source Support	Composite, S-video, Component, VGA, DVI,HDMI,SDI,HD-SDI
32	Control distance	UTP CAT5E: 100m, Multi-mode Fiber: 500m , Single-mode Fiber 10Km
Part V Package & Spare Part		
33	Package	Carton package inside of exterior wooden case (Free)
34	Spares parts	4 pcs modules, 2pc power supplies, 1 receiving card, 4 hub card, 1pcs Long power cable,1 pc long data cable, 15 pc short power cables,15 pc short data cables, 150 set RGB LEDs, several screws and accessories.
35		
36		
37		
38		