

## 200mm LED Traffic Signal Module Model No.: TL200D



### Product Features

Novel design with beautiful appearance  
Low power consumption  
High efficiency and brightness  
Large viewing angle  
Long lifespan: 80 000 hours

Multi-layer sealed and waterproof  
Visual distance:  $\geq 400\text{m}$   
Housing: Polycarbonate  
Exclusive optical diffuser lens and good color uniformity

Long viewing distance  
Wide temperature:  $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$   
CE, IP55, ITE Standard, RoHS,  
TUV, UL, EMC, LVD, WEEE,  
Svensk standard SS-EN 12368:2006


### Technical Parameters:

Article Number	Color	LED Qty	Light Intensity	Wave Length	Viewing Angle L/R	Viewing Angle U/D	Power	Working Voltage	Housing Material
TL200R	Red	61	$\leq 400\text{cd}$	$625 \pm 5 \text{ nm}$	$30^{\circ}$	$30^{\circ}$	6W	11-30VDC/VAC 85V-265VAC, 50/60HZ	PC, UV resistant
TL200Y	Yellow			$590 \pm 2 \text{ nm}$			5W		
TL200G	Green			$505 \pm 2 \text{ nm}$			7W		
TL200V	White			$6500\text{K}$			6W		
TL200B	Blue			$470 \pm 5 \text{ nm}$					

### Packing Info:

Carton Size	QTY	GW	NW	Wrapper	Volume (m3)
0,21 * 0,22 * 0,10 m	1 pcs /carton box	0,65 kg	0,8 kg	K=K carton	0,004

### Installation Sketch:



**Address**  
LED Light Scandinavia AB  
Lerklockan 8  
739 93 Riddarhyttan  
Sweden  
**Phone**  
+46 (0)73-679 35 50

**Company headquarters**  
Riddarhyttan  
**Bank**  
Handelsbanken  
**IBAN**  
SE09 6000 0000 0008 0664 0448  
**BIC**  
HANDSESS

**Bankgiro**  
548-7319  
**Organization no**  
556968-1157  
**VAT number**  
SE556968115701  
**Holds F-tax certificate**

**Internet**  
www.ledochled.se  
**E-mail**  
info@ledochled.se  
**Terms & delivery conditions**  
www.ledochled.se/villkor