

200mm LED Traffic Signal Module Model No.: TL200HE



Novel design with beautiful appearance
Low power consumption
High efficiency and brightness
Large viewing angle
Long lifespan: 80 000 hours

Product Features

Multi-layer sealed and waterproof
Visual distance: >400m
Housing: Polycarbonate
Exclusive optical lens and good color uniformity

Long viewing distance
Wide temperature: -40°C~+80°C
CE, IP65, ITE Standard, RoHS,
TUV, UL, EMC, LVD, WEEE,
Svensk standard SS-EN 12368:2006

Technical Parameters:

Article Number	Color	LED Qty	Light Intensity	Wave Length	Viewing Angle L/R	Viewing Angle U/D	Power	Working Voltage	Housing Material
TL200R	Red	6	≤400cd	625±5 nm	30°	30°	7W	11-30VDC/VAC 85V-265VAC, 50/60HZ	PC, UV resistant
TL200Y	Yellow			590±2 nm					
TL200G	Green			505±2 nm					
TL200V	White			6500K					
TL200B	Blue			470±5 nm					

Packing Info:

Carton Size	QTY	GW	NW	Wrapper	Volume (m3)
0,31 * 0,31 * 0,17 m	1 pcs /carton box	1,32 kg	1,6 kg	K=K carton	0,016

Installation Sketch:



Address
LED Light Scandinavia AB
Lerklockan 8
739 93 Riddarhyttan
Sweden
Phone
+46 (0)73-679 35 50

Company headquarters
Riddarhyttan
Bank
Handelsbanken
IBAN
SE09 6000 0000 0008 0664 0448
BIC
HANDSESS

Bankgiro
548-7319
Organization no
556968-1157
VAT number
SE556968115701
Holds F-tax certificate

Internet
www.ledochled.se
E-mail
info@ledochled.se
Terms & delivery conditions
www.ledochled.se/villkor